



# PRESTRESSING STRAND

NEDRI's prestressing steel guarantees the durability and quality of prefab construction, infrastructural and large industrial projects on-shore and off-shore, as years of satisfied customers can testify.

**NEDRI Product Range:**  
**Prestressing strand**

|  |   |
|--|---|
| <b>Range of dimensions</b>               | 7 wires: $\phi$ 6.9 - 18 mm<br>3 wires: $\phi$ 7.5 mm   |
| <b>Type</b>                              | thermomechanical heat treated (stabilised)  |
| <b>Relaxation</b>                        | extra low relaxation  |
| <b>Surface</b>                           | plain or indented   |
| <b>Profile</b>                           | according to Euronorm, or as agreed   |
| <b>Coil weight</b>                       | 2000 – 4000 kg  |
| <b>Coil sizes</b>                        | Internal diameter : 750 – 1200 mm<br>External diameter : 1150 – 1750 mm<br>Height : 530 - 800 mm  |
| <b>Cut length</b>                        | We deliver strand on cut length:<br>1000 – 6000 mm  |
| <b>Strand: greased and HDPE-sheathed</b> | 7 wires: $\phi$ 12.5 – 15.7 mm<br><br>If you need strand, which is not included in our product range, please do not hesitate to contact us. We will try to comply with your specifications regarding special dimensions, properties or packaging. Our technicians will be glad to help you find a technical and economic solution for your need |

NEDRI Spanstaal BV is ISO 9001 and 14001 certified by Lloyd's Register Quality Assurance and is a member of ESIS: European Stress Information Service.



Ask for our other product brochures as well