



**NEDRI Product Range:  
Prestressing wires**

# PRESTRESSING WIRES

NEDRI's prestressing steel guarantees the durability and quality of prefab construction, infra structural and large industrial projects on-shore and offshore, as years of satisfied customers can testify.

<b>Range of dimensions</b>	ø 4.0 – 11 mm
<b>Type</b>	as drawn or thermo mechanical heat treated (stabilised)
<b>Relaxation</b>	extra low relaxation
<b>Surface</b>	plain or indented
<b>Indentation</b>	according to Euronorm or on your specification
<b>Coil/ ring weight</b>	500 – 2700 kg
<b>Ring sizes</b>	Inside diameter : 1000 - 2000 mm Outside diameter : 1200 - 2420 mm Height : 140 - 290 mm
<b>Coil sizes</b>	Inside diameter : 580 - 1090 mm Outside diameter : 1300 - 1450 mm Height : 460 - 890 mm
<b>Wire on cut length</b>	We deliver wire on cut length: 1000 – 6000 mm If required we can thread the cut wire.
<b>Bundle weight</b>	600 – 2700 kg  If you need wire, which is not included in our product range, please do not hesitate to contact us. We will try to comply with your specifications regarding special dimensions, properties or packaging. Our technicians will be glad to help you find a technical and economic solution for your needs.

Ask for our other Product brochures as well

NEDRI Spanstaal BV is ISO 9001-2015 and ISO 14001 : 2015 certified by Lloyd's Register Quality Assurance and is a member of ESIS: European Stress information Service